

5 12d Synergy Enabled

# 12d Track

12d Track has been specifically designed for the survey, design and construction of light, heavy and high speed rail projects.

Extensive railway tools in 12d Track allow the rail designer to quickly and easily design their projects. These options are built on the existing 3D modelling and design tools available in 12d Model.

12d's integrated railway design module can be utilised to develop detail railways designs. It is fully customisable to meet any design standard with numerous tools to assist with design automation.

#### **Turnout Create/Edit**

The "Turnout Create/Edit" panel allows the user to enter parameters for turnouts such as Lead Length, IP to Heel Length and Turnout Angle.

This tool will also be developed to include all special trackwork elements that may be required by a rail designer such as Similarflexure, Contraflexure, Tangential and Dual Gauge turnouts.



The "Turnout Place" panel to setout turnouts along an alignment will then use the parameters entered. The gauge and rail radii are also entered and these can be plotted for visualisation purposes.



Extensive railway tools in 12d Track allow the rail designer to quickly and easily design their projects Setout tables for sleeper sets can also be added to a turnout to allow sleepers to be plotted by setout distances along the stockrails and is useful for visualisation purposes.

	tails Swite	h Design C	crossing Design	Closure	Design Sle	eper Details	1			
Crossing D	esign									
1 in			4							
Ang = 2*	(Atan(0.5/)	ing number)	)							
Ang = At	tan(1/xing_	number)	Г							
		3*34'35"	2							
Crossing	point width	h	4							
Crossing	toe length									
Crossing	heel length	, <u> </u>								
				1						
choice	ok		_				Set   Da	elete Dele	te All Finish	Help
, enonce						_				
nouts Cre	ate/Edit V	er 1.03								1
nouts Cre	ate/Edit V gs	er 1.03	Carl				abal Tre			
nouts Cre nout Settin ype QLD	ate/Edit V gs 16560kgTii	er 1.03 mbe 🔐	Configuration	n Standa	rd	<b>V</b> 1	abel 1in10	5 STANDAF	RD (60kg on tim	nber)
nouts Cre nout Settin ype QLD urnout Deta	<mark>ate/Edit V</mark> gs 116S60kgTii ails   Switc	er 1.03 mbe 🔐 h Design   Ci	Configuration	n Standa Closure D	rd Iesign Slee	∎ L per Details	abel 1in10	5 STANDAR	RD (60kg on tim	nber)
nouts Cre nout Settin ype QLD urnout Deta	ate/Edit V gs 116S60kgTi ails   Switc	er 1.03 mbe 📧 h Design   Cr	Configuration rossing Design	n Standa Closure D	rd Iesign Slee	per Details	abel [lin10	5 STANDAF	RD (60kg on tim	nber)
nouts Cre nout Settin ype QLD urnout Deta Sleeper Name	ate/Edit V gs 16S60kgTii ails Switc Details	er 1.03 mbe 😹 h Design   Cr	Configuration rossing Design	n Standa Closure D	rd Hesign Stee	per Details	abel 1in10	5 STANDAF	:D (60kg on tim	nber)
nouts Creation out Settin ype QLD urnout Deta Sleeper Name Time	ate/Edit V gs 116S60kgTii ails Switc Details SL04	er 1.03 mbe 🗟 h Design   Ci	Configuration rossing Design	Closure D	rd Jesign Slee	per Details	abel linit	5 STANDAF	1D (60kg on tim 200	lber)
nouts Cre nout Settin ype QLD mout Det. Sleeper Name Type	ate/Edit V gs 116S60kgTii ails   Switc Details  SL04  FS9150 al Ta	er 1.03 mbe 😖 h Design   Ci -SL04	Configuration rossing Design	n Standa Closure D ffset [	rd lesign Slee 0.250 -0.705	per Details	abel 1in10	5 STANDAF	1D (60kg on tim 200 0.705	let in the second secon
nouts Cre nout Settin ype QLD urnout Det. Sleeper Name Type Materi	ate/Edit V gs 18560kgTii ails   Switc Details   SL04   FS9150 al   Timber	er 1.03 mbe 📧 h Design   Cr -SL04	Configuration rossing Design Width Straight o Straight e	n Standa Closure D ffset [ xtension ]	rd tesign Slee 0.250 -0.705 0.541	eper Details	Depth Curved of Curved ex	5 STANDAF [0. fset [-( tension [0.	1D (60kg on tim 200 0.705 541	land the second
nouts Cre nout Settin ype QLD urnout Deta Sleeper Name Type Materi	ate/Edit V gs 16560kgTii ails Switc Details SL04 F59150 al Timber Set Sleep	er 1.03 mbe el ci h Design Ci -SL04	Configuration rossing Design N Width Straight o Straight e Append Si	n Standa Closure D ffset [ xtension ] leeper]	rd tesign Slee 0.250 -0.705 0.541	per Details	abel 1in10	5 STANDAF 0. fset -0 tension 0. De	1D (60kg on tim 200 0.705 541 lete All Sleeper:	lber)
nouts Cre nout Settin ype QLD urnout Det Sleeper Name Type Materi	ate/Edit V gs 116560kgTii ails Switc Details SL04 FS9150 al Timber Set Sleep	er 1.03 mbe exi h Design Cr -SLO4	Configuration rossing Design N Width Straight o Straight e Append SI	n Standa Closure D ffset [ xtension ] leeper]	rd tesign Slee 0.250 -0.705 0.541	Per Details	abel 1in10 Depth Curved of Curved ex per	5 STANDAF 0. fset -( tension 0. De	1D (60kg on tim 200 0.705 541 lete All Sleepen	rber)
nouts Cre nout Settin ype QLD urnout Det Sleeper Materi	ate/Edit V gs 16560kgTii ails   Switc Details  SL04  FS9150 al  Timber  Set Sleep  Table	er 1.03 mbe et h Design Cr	Configuration rossing Design N Width Straight of Append SI	n Standa Closure D ffset [ xtension ] leeper	rd tesign Slee 0.250 0.541	L sper Details	abel 1in10 Depth Curved of Curved ex per	5 STANDAF [0. fset [-( tension [0. De	ID (60kg on tim 200 0.705 541 Jete All Sleeper	sber)
nouts Cree nout Settin ype QLD imout Deta Sleeper Materi Sleeper	ate/Edit V gs 16560kgTii ails Switc Details SL04 FS9150 al Timber Set Sleeper Table	er 1.03 mbe es h Design Cr -SL04	Configuration rossing Design   N Width Straight o Straight e Append SI	n Standa Closure D ffset [ stension ] leeper]	rd tesign Slee 0.250 0.541	L sper Details	.abel 1in10 Depth Curved of Curved ex per	5 STANDAF 0. fset -( tension 0. De	D (60kg on tim 200 3.705 541 Jete All Sleeper	sber)
nouts Cree nout Settin ype QLD imout Deti Sleeper Materi Sleeper	ate/Edit V gs 116560kgTii ails Switc Details SL04 F59150 al Timber Set Sleep Table Name SL02	er 1.03 mbe est h Design Cr -SL04 er Type Egg160.~S	Configuration rossing Design   Width Straight of Straight of Append St Append St U2 Timber	fiset [ teeper]	rd lesign Slee 0.250 -0.705 0.541 Depth 0.200	Delete Sleep	_abel 1in10 Depth Curved of Curved ex per Curv Off.	5 STANDAF 0. fset -( tension 0. De Str Ext. 0.541	D (60kg on tim 200 7.705 541 lete All Sleeper	speil
nouts Creatin ype QLD urnout Deta Sleeper Name Type Materi	ate/Edit V gs 116560kgTii ails Switc Details SL04 F59150 al Timber Set Sleep Table Name SL02 SL03	er 1.03 mbe est h Design Cr -SL04 er FS9150-S FS9150-S	Configuration rossing Design   Width Straight o Straight o Append Si Material L02 Timber J03 Timber	n Standa Closure D ffset [ stension ] leeper] Width 0.250 0.250	rd tesign Slee 0.250 -0.705 0.541 Depth 0.200 0.200	Delete Sleep	Depth Curved of Curved ex per -1.865 -1.285	5 STANDAF [0, fset -( tension [0, De Str Ext. 0.541 0.541	D (60kg on tim 200 2.705 541 lete All Sleeper 0.541 0.541	ber) [
nouts Creatin ype QLD urnout Deta Sleeper Materi	stc/(Edit V) gs 116560kgTii ails   Switc Stud FS9150 al   Timber Set Sleep Table Name SL03 SL03	er 1.03 mbe m h Design Cr SL04 er Type FS9150-S FS9150-S FS9150-S	Configuration rossing Design   M Width Straight or Straight or Append SI Material L02 Timber L03 Timber L03 Timber	n Standa Closure D ffset [ stension ] leeper] Width 0.250 0.250	rd tesign Slee 0.250 -0.705 0.541 0.541 0.200 0.200 0.200	L per Details Delete Sleep Str Off. -1.885 -1.285 -0.705	Depth Curved of Curved of Curved ex per -1.865 -1.285 -0.705	5 STANDAF 5 STANDAF 6 Strest 0.541 0.541 0.541 0.541	1D (60kg on tim 200 3.705 541 lete All Sleeper 0.541 0.541 0.541 0.541	sber)
nouts Crei nout Settin ype QLD imout Det Sleeper Name Type Materi	stc/Edit V gs 16560kgTii ails Switc Sto4 FS9150 al Timber Set Sleep Name SL02 SL03 SL04 SL05	er 1.03 mbe ell h Design Cr -SL04 er Type FS9150-S FS9150-S FS9150-S FS9150-S FS9150-S FS9150-S	Configuration rossing Design Width Straight o Straight o Append SI U2 Timber L03 Timber L04 Timber	ffset [ width 0.250 0.250 0.250	rd tesign Slee 0.250 0.541 Depth 0.200 0.200 0.200 0.200	Lefter Sieger Str Off. -1.865 -1.285 -0.705 -0.125	abel         1in10           Depth         Curved of           Curved of         Curved ex           per         -1.865           -1.865         -0.705           -0.125         -0.125	5 STANDAF 5 STANDAF 6 Str Ext. 0.541 0.541 0.541 0.541	D (60kg on tim 200 ).705 541 lete All Sleeper O.541 0.541 0.541 0.541	s
nouts Cree nout Settin ype QLD arnout Deta Name Type Materi	stc/(dit V gs 116560kgTii ails Switc Details SL04 F59150 al Timber Set Sleep Table Name SL02 SL03 SL03 SL04 SL05	er 1.03 mbe el h Design Cr -SL04 er Type FS9150-S FS9150-S FS9150-S FS9150-S FS9150-S FS9150-S	Configuration rossing Design   Width Straight of Straight of Append SI Material L02 Timber L03 Timber L03 Timber L03 Timber L04 Timber L04 Timber	n Standa Closure D ffset f ktension f leeper Width 0.250 0.250 0.250 0.250 0.250	rd tesign Slee 0.250 0.541 Depth 0.200 0.200 0.200 0.200	Image: Details           Image: Details	Depth Curved of Curved of Curved ex per Curved ex per Curved ex per -1.865 -1.285 -0.705 -0.125 Sa	5 STANDAR fset [-( tension [0, 	D (60kg on tim 200 1705 541 Iete All Sleeper 0.541 0.541 0.541 0.541 0.541 0.541	sber)
nouts Cree nout Settin ype QLD arnout Deta Sleeper Materi	ste/(dit V gs 116560kgTii ails Switc SL04 F59150 al Timber Set Sleep Table Name SL02 SL03 SL04	er 1.03 mbe h Design SL04 er FS9150-S FS9150-S FS9150-S FS9150-S FS9150-S	Configuration rossing Design   Width Straight of Straight of Append Si Material U22 Timber L04 Timber L05 Timber L05 Timber	ffset [ transient filesent fi	rd etesign Slee 0.250 0.705 0.541 0.200 0.200 0.200 0.200 0.200 0.200	Image: Details           Image: Details	Depth Curved of Curved of Curved ex per -1.865 -1.285 -0.705 -0.125 -0.125 Sa	5 STANDAR fset	D (60kg on tim 200 7.705 541 lete All Sleeper Curv Ext. 0.541 0.541 0.541 0.541 0.541	sber)

#### **Turnout Reader/Writer**

Tools for writing turnout parameters to an ASCII file and reading them back in to another project are provided.

#### Place Turnouts

The "Place Turnouts" panel allows the rail designer to place a turnout into an alignment using a 12d function.

The positioning of the turnout is based on the chainage and direction of the turnout and the insertion point can be varied between the TOS, IP or one of the two APC points.

Turnouts can be places by various geometric "Reference"

🖪 Turnout Place	_ 🗆 🗙
Place Turnout	
Function	<u>f</u> *
Reference Geometry Reference Type at chainage	
Reference String	1
Direction Normal	
Chainage Offset	F
Chainage	<del>د ۲</del>
Turnout Details	
Turnout Name	N
Туре	abd
Placement Node TOS	
Placement Side Left	
Centrelines Model	<b>N</b>
Tangents Colour	
Centreline Colour	
Show Rails Show Sleepers Import 12da File	
Show Rails	
Plot Rails	
Rail Model 📃 😒	
Rail Colour	
choice ok	
Place Turnout Finish Help	



calculations relative to alignments such as "by chainage", "by vertex" and "by dropped point". The turnout is positioned according to the geometric data provided and should an alignment move the turnout will move also.

The "Place Turnouts" option is also able to plot the rails and sleepers for visualisation purposes.

Turnouts placed with functions can be self-positioning using several insertion "nodes" such as "Toe of Switch", "Intersection point" or on

alignment opposite the "Theoretical Crossing point".

The turnouts are placed as functions so they automatically select the Horizontal Bearing and Vertical Grades directly off the chosen Alignment String.

They can be placed either in the same direction or opposite direction to the Alignment String.

## **Cant Calculation**

The "Cant Calculator" panel is used to calculate cants along an alignment. Rate of change of Cant and Cant Deficiency are calculated based on the gauge constants entered into the panel.

Particular curve constants for any gauge can be entered into the panel or one of three typical gauges can be selected. The data can also be exported to an excel spreadsheet.

#### **Plot Rails**

Rails can be plotted using the "Plot Rails" panel. This option uses the cant calculations and gauge to plot the rail levels at a regular interval along the alignment. Rail extrusion techniques can be used in 12d to produce a visualisation of the project.

Cant panel		
Rail CL Alignment	RATI CLINEW MC	
Speed	BO 123	
Gauge		
Virtual Cant	20	
Cant Elements		
0.000 ARC1		
115.244 ARC2		
206 650 500 2		
Element Data		
Туре	ARC1	abo
Speed	80	123
Chainage	0	2
Radius	299.4	<u>۴</u>
Eq Cant	252,6653	
App Cant	152	123
	CEDT   DELETE   DELE	
ARC1 Ch: 0.000	R: 299.400m V: 80km/r	nr 🔺
Ce: 252.7mm	Ca: 152mm Def: 100.7	mm
dist: 115.244	m Roc: 1in0.0 RocDef: 0.0	)mm/s
ARC2 Ch: 115.2	2441 R: 299.4000m V: 80	)
Ce: 252.7mm	Ca: 152mm Def: 100.7	mm



## **Advanced Rail Alignments**

12d alignments also have the ability to be generated by joining elements that are fixed in position or can have various degrees of freedom to float into place relative to adjacent elements whose positions have been resolved based on their own location parameters.

Computated rail alignments are alignments that are positioned relative to other rail alignments. These alignments have the ability to reposition automatically should the reference alignments move.

Function		f.
Rail Detai	s Extrude De	tails
Rail Det	ails	
	Reference St	tring
	Name	N
	Model	
	Colour	
	Interval	
Plot Rails	Finish He	lp

In conjunction with the turnout placement tool a group of rail alignments can be generated that are self calculating based on the choices of turnouts made.

# **Chainage Equalities**

Chainage equalities can be placed at any point along an alignment using several methods of definition. These can be point equalities at any chainage or offsets calculated from Kilometre posts.



# **Rail Transitions**

12d calculates various Rail Transition types such as Clothoid, Cubic spiral and Cubic Parabola.

# **Calculate Centre from Rails**

The "Calculate centreline points from rails" panel generates a sequence of points between two surveyed rail strings. These points can be used to check slew and best fit between alignments generated by 12d and the original surveyed rail alignment.



The tool also develops strings across the rails representing the "Low Rail Height". These can be viewed in a long section of an alignment to determine the track lift and lower along the alignment. The "Slew-Calculation" panel also plots the radius at each point based on the versine of surrounding points.







#### **Roads and Highways**

12d Model's design option is the smarter solution for the design, modification and maintenance of Road and Highway projects.

Enjoy advanced 3D tools to design local and major roads, intersections, roundabouts, highways, interchanges and much more.



#### Land Development

12d Model is the most versatile solution for the creation of sustainable land development projects, including residential, commercial and industrial developments, recreational areas, landfills, and agriculture projects.

Easily manage all aspects of your land development project from earthwork quantities, road design utilities and drainage design.



#### Rail

12d Track has been specifically designed for the survey, design and construction of light, heavy and high speed rail projects.

Extensive railway tools in 12d Track allow the rail designer to quickly and easily design their projects. These options are built on the existing 3D modelling and design tools available in 12d Model.



#### Drainage, Sewer and Utilities

12d Model provides comprehensive tools for the design, analysis and optimisation of stormwater and sewer projects using rational, dynamic (hydrograph) and 2d drainage methods.

Powerful clash detection management allows for efficient 3D modelling of service networks such as gas, electricity, telecommunications and water prior to construction.



#### Oil and Gas

12d Model assists with the design, construction and mapping of oil and gas pipelines, original site exploration and the wide range of infrastructure required for oil and gas projects.

Accurate 3D modelling and the ability to share data between users allow teams to quickly and easily coordinate designs.



## Rivers, Dams and Hydrology

12d Model handles very large datasets and interfaces with a wide range of analysis packages, making it perfect for flood studies and the management of rivers and dams.

12d has partnered with industry leading analysis software, allowing users to apply 2D drainage analysis from within 12d Model.



- Powerful data processing & intelligent functionality.
- Modular, easy to update & completely customisable.
  Seamless integration with major industry software
- and hardware.
- Used in over 55 countries worldwide.
- Friendly support & training from industry experts.



## Ports and Dredging

12d Model is the solution for port infrastructure and dredging, easily managing the very large datasets and complex volume calculations often required by these projects.

A complete range of flexible and customisable volume calculation tools allow teams to extract and present the information quickly and easily.



# Airport Infrastructure

12d Model provides a solution for the design, construction and analysis of new airports, as well as the upgrade and maintenance of existing runways and airport infrastructure.

Easily manage large airport infrastructure projects and share data across multi-disciplinary teams.



#### **Mining Infrastructure**

12d Model's powerful set of exploration, site investigation, survey and analysis tools are crucial for the initial design, construction and ongoing operation of mining projects.

Comprehensive tools for the survey, design and construction of access roads, railways, earthworks and services allow for the coordinated design and management of mining infrastructure from within 12d Model.



## Surveying

12d Model is a complete surveying package providing the tools to manage all facets of surveyed data including LIDAR, topographical, as-built, conformance, traversing, geodetics, data mapping, labelling and much more.

The 12d Field option runs on a ruggedized tablet and gives the user access to full 12d Model functionality, allowing you to take the entire project into the field with the most comprehensive pick-up and set-out tools.



# Construction

12d Model is the ultimate software for construction with powerful set-out options, direct interfaces to machine control and detailed conformance reporting and auditing.

Manage 3D data and control volumes, quantities and progress claims with 12d Model. Set-out your project and undertake conformance and as-built surveys live on-site using 12d Field.



# Environmental

12d Model's ability to handle very large datasets combined with flexible and comprehensive 3D analysis and modeling tools make it perfect for a wide variety of environmental projects.

Existing workflows can adopt 12d Model easily as it allows users to directly interface with GIS systems and most software packages and file formats.

#### CONTACT US TODAY

E info@12d.com P +61 2 9970 7117

W www.12d.com

12d Solutions Pty Ltd PO Box 351 Narrabeen NSW 2101 Australia © 2018 12d Solutions Pty Ltd

